



FORWARD LIFT®

ENGINEERED TO PERFORM. BUILT TO LAST.



Car and truck lifts to meet your every need.

Reliable lift systems for independent repair shops, car dealerships, body shops, home enthusiasts, and heavy-duty truck facilities.





BP9113000BL

BP9

9,000 lbs. CAPACITY

FEATURES:

- Symmetrical column design
- Low ceiling two post lift
- 2-stage symmetric arms
- Carriage latch system – engages every 3"
- Secondary lock system includes a spring actuated slack chain locking device
- Dual hydraulic cylinders
- Powder coated finish

INCLUDES LOW-PROFILE THREADED ADAPTERS AND (4 each) ADAPTER EXTENSIONS AT 3.5" and 5"



SPECIFICATIONS **BP9113000BL/RD***

Capacity	9,000 lbs. (4082kg)
Overall Height	111-1/4" (2825mm)
Overall Width	138-1/2" (3517mm)
Rise	72" (1828mm)
Maximum Rise	80-1/2" (2044mm) w / 5" extension
Drive Through Clearance	97-1/4" (2470mm)
Width Inside column	111" (2819mm)
Arm Reach (Min/Max)	30" / 46-1/4" (762mm/1174mm)
Minimum Adapter Height	4-1/2" (114mm)
Drive-over Height	1-1/2" (38mm)
Voltage/Amps	208V/230V, 17 amps
Motor/Phase	1ph/2HP
Ceiling Height Required	113" (2870mm)



F10N400MBL

F-10

10,000 lbs. CAPACITY

FEATURES:

- Symmetrical column design
- Versatile 3-stage front and 2-stage rear arms
- Top mounted Direct-Pull lifting technology
- Cylinder rod concealed inside carriage
- Adjustable width options
- Powder coated finish
- Includes adapter storage bracket

INCLUDES LOW-PROFILE DROP-IN ADAPTERS AND (4 each) ADAPTER EXTENSIONS AT 3.5" and 5"



SPECIFICATIONS **F10N400MBL/RD***

Capacity	10,000 lbs. (4535kg)
Maximum Rise	76 -1/4" (1937mm) w / 5" extension
Overall Height	143" (3632mm)
Overall Width	131" or optional 137" (3327mm/4380mm)
Drive through Clearance	99" or optional 105" (2515mm/2667mm)
Overhead Switch Height	137-1/4" (3486mm)
Front Reach (Min/Max)	24-1/2" / 44-3/8" (621mm/1127mm)
Rear Reach (Min/Max)	36" / 58" (914mm/1473mm)
Min/Max Adapter Height	3-3/4" (95mm) w/o adapter extension 8-3/4" (222mm) w / 5" adapter extension
Width Inside Columns	109" or optional 115" (2769mm/2921mm)
Voltage/ Amps	208V/230V, 17 amps
Motor/Phase	1ph/2HP/60Hz
Ceiling Height Required	144" (3658mm)



I10N400MBL

I10

10,000 lbs. CAPACITY

FEATURES:

- Symmetrical column design
- Spot-Rite™ 3-stage front arm design
- Spot vehicles asymmetrically or symmetrically
- Top mounted Direct-Pull lifting technology
- Cylinder rod concealed inside carriage
- Adjustable width options
- Powder coated finish
- Includes adapter storage bracket

INCLUDES LOW-PROFILE THREADED ADAPTERS AND (4 each) ADAPTER EXTENSIONS AT 3.5" and 5"



SPECIFICATIONS **I10N400MBL/RD***

Capacity	10,000 lbs. (4535kg)
Maximum rise	76 -1/4" (1937mm) w/5" extension
Overall Height	143" (3632mm)
Overall Width	131" or optional 137" (3327mm/4380mm)
Drive through clearance	99" (2515mm) or optional 105" (2667mm)
Overhead switch height	137-5/8" (3496mm)
Front reach (Min/Max)	23" / 44-3/8" (584mm/1127mm)
Rear reach (Min/Max)	36" / 58" (914mm/1473mm)
Min/Max adapter height	3-3/4" (95mm) w/o adapter extension 8-3/4" (222mm) w / 5" adapter extension
Width inside column	109" or optional 115" (2769mm/2921mm)
Voltage/ Amps	208V/230V, 17 amps
Motor/Phase	1ph/2HP/60Hz
Ceiling height required	144" (3658mm)



F12N300BL

F-12

12,000 lbs. CAPACITY

FEATURES:

Symmetrical column design

Four height configuration models
2-stage front and rear arms

- Adjustable width options
- Powder coated finish
- Includes adapter storage bracket

INCLUDES LOW-PROFILE DROP-IN ADAPTERS AND (4 each) ADAPTER EXTENSIONS AT 3.5" and 5"



SPECIFICATIONS	F12N300BL/RD*
Capacity	12,000 lbs. (5443kg)
Maximum Rise	77-1/2" (1968mm) w/5" extension
Adjustable Overall Height Options	F12N300 166" (4216mm) Standard
	F12N301 178" (4521mm) Max. Height
	F12N302 154" (3912mm)
	F12N303 143" (3632mm)
Overall Width	140" (3556mm) or optional 146" (3708mm)
Drive through clearance	108-3/4" (2762mm) or optional 102-3/4" (2610mm)
Overhead switch height Options	F12N300 160-1/8" (4067mm) Standard
	F12N301 172-1/8" (4524mm) Extended
	F12N302 148-1/8" (3762mm)
	F12N303 137-1/8" (3483mm)
Front reach (Min/Max)	35" / 54" (889mm/1372mm)
Rear reach (Min/Max)	35" / 54" (889mm/1372mm)
Min/Max Adapter Height	4-3/4" (121mm) w/o extension
	9-3/4" (248mm) w/5" extension
Width Inside Columns	120-7/8" (3070mm) Adjustable
	114-7/8" (2918mm) Standard
Voltage/Amps	208V/230V, 17 amps
Motor/Phase	1ph/2HP/50Hz; 1ph/2HP/60Hz
Ceiling Height Required	168" (4267mm)



I12N300BL

I-12 PRO

12,000 lbs. CAPACITY

FEATURES:

Symmetrical column design

Four height configuration models
Versatile 3-stage front and rear arms

- Adjustable width options
- Models for most ceiling heights
- Powder coated finish
- Includes adapter storage bracket

INCLUDES LOW-PROFILE DROP-IN ADAPTERS AND (4 each) ADAPTER EXTENSIONS AT 1.75", 3.5" and 5"



SPECIFICATIONS	I12N300BL/RD
Capacity	12,000 lbs. (5443kg)
Maximum Rise with 5" Extension	80-3/4" (2051mm)
Adjustable Overall Height Options	I12N300 166" (4216mm) Standard
	I12N301 178" (4521mm) Max. Height
	I12N302 154" (3912mm)
	I12N303 143" (3632mm)
Overall Width	140" (3556mm) or optional 146" (3708mm)
Drive through clearance	108-3/4" (2762mm) or optional 102-3/4" (2610mm)
Overhead Switch Height Options	I12N300 160-1/8" (4067mm) Standard
	I12N301 172-1/8" (4524mm) Extended
	I12N302 148-1/8" (3762mm)
	I12N303 137-1/8" (3483mm)
Front Reach (Min/Max)	27-3/4" / 59" (705mm/1460mm)
Rear Reach (Min/Max)	27-3/4" / 59" (705mm/1460mm)
Min/Max Adapter Height	4-3/4" (121mm) w/o extension
	9-3/4" (248mm) w/5" extension
Width inside Columns	120-7/8" (3070mm) Adjustable
	114-7/8" (2918mm) Standard
Voltage/Amps	208V/230V, 17 amps
Motor/Phase	1ph/2HP/50Hz; 1ph/2HP/60Hz
Ceiling Height required	168" (4267mm)



DP18N002BL

DP15

15,000 lbs. CAPACITY

DP18

15,000 lbs. CAPACITY

FEATURES:

Symmetrical column design
Three height configuration models
2-stage front and rear arms

- Top mounted Direct-Pull lifting technology
- Powder coated finish
- Includes adapter storage bracket

INCLUDES LOW-PROFILE THREADED ADAPTER PADS AND (4 each) ADAPTER EXTENSIONS AT 5" and 10"



SPECIFICATIONS	DP15N000BL/RD* DP18N000BL/RD*
Capacity	15,000 lbs. (6803kg)
	18,000 lbs. (8164kg)
Maximum Rise with 10" Adapter Extensions	83" (2120mm)
Overall Height	DP15 / DP18N000 154-3/4" (3930mm)
	DP15 / DP18N001 175" (4445mm)
	DP15 / DP18N002 199" (5054mm)
Height to Shut-Off	147-1/4" (3735mm)
Overall Floor Width	154-3/8" (3921mm)
Width Inside Columns	119-5/8" (3038mm)
Drive Through Clearance	108-1/4" (2750mm)
Arm Reach (Min/Max)	38" / 61" (965mm/1549mm)
Min. Adapter Height	5-1/2" (139mm)
Max. Adapter Height with 10" Extension	15-1/2" (393mm)
Voltage/Amps	208V/230V, 17 amps
Motor/Phase	1ph/2HP
Ceiling Height Required	155-3/4" (3956mm)



Shown: FSA14N0110BL

FSA14 ALIGNMENT LIFT FEATURES:

- Configured for vehicles with longer wheelbases with oversized slip plates and adjustable radius gauge pockets.
- Four-wheel alignments with wheelbases from 85.5" up to 193"
- Two 7,000 lbs. Rolling Jacks, Two Turning Radius Gauges included
- Air actuated locking rear slip plate

FS14

**14,000 lbs. Capacity
General Service**

FSA14

**14,000 lbs. Capacity
Alignment Service**

FEATURES:

- 18' runways accommodate a range of wheelbases
- Open scissor design = greater vehicle access
 - 198" max wheel base for general service
 - Folding ramps with rear wheel chocks
 - 40" between platforms for more access
 - 25-1/2" wide runways
 - Recessed / surface mount options

SPECIFICATIONS	Alignment Models FSA14N0110BL/RD Gen. Service Model FS14N0010BL/RD	
	Maximum Rise*	72 - 3/4" surface mounted
Maximum Wheelbase	198"	
Minimum 4 Wheel Alignment	85-1/2" NA	
Maximum 4 Wheel Alignment	193" NA	
Lowered Height	10 - 3/4"	
Overall Length	277"	
Overall Width	91"	
Runway Width	25 - 1/2"	
Width Between Platforms	40"	
Runway Length	216"	
Motor / Voltage	Single Phase - 5 HP / 230V	
Time of Full Rise	77 seconds	
Compressed	85 - 110 psi	

* Surface mounted lift.

Lifts are available in red and blue - power unit consoles are gray



FS77N0000MBL

FS77

7,700 lbs. Capacity

FEATURES:

Exclusive Inverse Piston Synchronization equalization system ensures worry-free use

- Low drive-over height allows for easy vehicle positioning
- 24-3/4" wide platforms accommodate a wide range of vehicles and pickup points
- Hinged ramps drop down to a 65 degree angle for easy access for wheel and brake service
- Durable, diamond plate finish
- Patent pending equalization system •
- Surface or flush mounted option

SPECIFICATIONS	FS77N0000MBL/RD	
Capacity	7,700 lbs. (3500kg)	
Maximum Rise	78-5/8" (2000mm) surface mounted 74-1/2" (1895mm) recessed mounted	
Lowered Height	4-1/8" (105mm)	
Overall Width	85" (2159mm)	
Overall Length	85" (2159mm)	
Platform width	24-3/4" (629mm)	
Width Between Platforms	23-5/8" (600mm)	
Platform Length	59" (1499mm) 85" (2159mm) w/ramps extended	
Ramp Length	13" (330mm)	
Max. Distance from Console to Lift	85" (2159mm)	
Voltage	230V	
Motor/Phase	1ph/4HP/60Hz	
Rise Time	39 seconds	
Compressed Air Connection	85-110psi	


 CRA14
CRA14N201YBL

CR14

**14,000 lbs. Capacity
General Service**

CRA14

**14,000 lbs. Capacity
Alignment Service**

FEATURES:

Two model lengths available

CR14 LIFT OPTIONS:

- Bolt-on, runway alignment kit with turning radius gauges
- Two 7,000 lbs. Rolling Jacks
- Internal airline kit

CRA14 INCLUDES:

- Two (2) 7,000 lbs. Capacity Rolling Jacks
- Carbon steel front radius plates
- Self-chocking 41" approach ramps with protective strips
- Rear wheel slip plates
- Internal airline standard
- FLR (filter, lubricator, regulator)

- 78-3/4" rise height provides better vehicle service access
- Heavy duty high-performance cable and sheaves system
- Easy to use single point lift operation with one button air operated lock release
- Multi-position lock components allow lift to be level at any lock position
- Self-chocking 41" approach ramps with protective strips
- Durable powder coat finish

CR LIFT SERIES OPTIONS:

- Drive-through ramps
- 3-phase motor
- Runway lighting

SPECIFICATIONS	CR14N201YBL/RD CR14N202YBL/RD	CRA14N201YBL/RD CRA14N202YBL/RD
	Capacity	14,000 lbs. (6350kg)
Maximum Wheelbase	182-1/2" (4635mm) 215" (5461mm)	182-1/2" (4635mm) 215" (5461mm)
Maximum Two Wheel Alignment	N/A	166-1/4" (4225mm) 199-1/4" (5060mm)
Maximum Four Wheel Alignment	N/A	157" (3987.8mm) 172-1/4" (4375mm)
Minimum Four Wheel Alignment	N/A	88" (2235mm)
Rise	78-3/4" (2000mm)	80-3/4" (2000mm)
Overall length	250" (6350mm) 283" (7188mm)	250" (6350mm) 283" (7188mm)
Overall width	131-3/4" (3346mm)	131-3/4" (3346mm)
Width Inside Columns	116-1/4" (2953mm)	116-1/4" (2953mm)
Length between Columns	195-1/4" (4959mm) 228-1/4" (5798mm)	195-1/4" (4959mm) 228-1/4" (5798mm)
Overall height	90-1/2" (2281mm)	90-1/2" (2281mm)
Runway width	20" (508mm)	20" (508mm)
Runway Height	7" (178mm)	9" (228mm)
Width Between Runways	43" (1092mm) or 46" (1168mm)	43" (1092mm) or 46" (1168mm)
Front of Runway to Center of Radius Gauge	N/A	22-11/16" to 52-11/16" (576mm-1338mm)
Rise Time	72 seconds	72 seconds
Motor	2HP	2HP
Minimum Bay Size	15' x 26' (4572mm x 7925mm) 15' x 28' (4572mm x 8534mm)	15' x 26' (4572mm x 7925mm) 15' x 28' (4572mm x 8534mm)



OR14

OR14N100YBL

OR14 INCLUDES:

- Two (2) 7,000 lbs. Capacity Rolling Jacks
- Carbon steel front radius plates
- Self-chocking 41" approach ramps
- Rear wheel slip plates
- Internal airline standard
- FLR (filter, lubricator, regulator)

CR014
14,000 lbs. Capacity
General Service

OR14
14,000 lbs. Capacity
Alignment Service
OPEN FRONT LIFTS

FEATURES:

Two model lengths available
Open front allows greater vehicle access

- 80-3/4" rise height provides better vehicle service access
- Patented articulating shaft design ensures even roller loading
- Heavy duty high-performance cable and sheaves system
- Durable powder coat finish

LIFT OPTIONS:

- Drive-through ramps
- LED runway light kit
- 3-phase motor

SPECIFICATIONS	CR014N201YBL/RD CR014N202YBL/RD	OR14N101YBL/RD OR14N102YBL/RD
Capacity	14,000 lbs. (6350kg)	14,000 lbs. (6350kg)
Maximum Wheelbase	182-1/2" (4635mm) 215" (5461mm)	182-1/2" (4635mm) 215" (5461mm)
Maximum Two Wheel Alignment	N/A	176 1/4" (4476mm) 209" (5308mm)
Maximum Four Wheel Alignment	N/A	164 3/4" (4184mm) 164 3/4" (4184mm)
Minimum Four Wheel Alignment	N/A	89" (2260mm) 89" (2260mm)
Rise	78 3/4" (2000mm)	78 3/4" (2000mm)
Overall length	253" (6426mm) 286" (7264mm)	253" (6705mm) 286" (7213mm)
Overall width	140-1/2" (3567mm)	140-1/2" (3567mm)
Width Inside Columns	116-1/4" (2953mm)	116 1/4" (2953mm)
Length between Columns	194-3/4" (4946mm) 227-3/4" (5784mm)	194-3/4" (4946mm) 227-3/4" (5784mm)
Overall height	109-1/16" (2770mm)	109-1/16" (2770mm)
Runway width	20" (508mm)	20" (508mm)
Runway Height	7" (178mm)	7" (178mm)
Width Between Runways	43" (1092mm)	43" (1092mm)
Front of Runway to Center of Radius Gauge	N/A	16" to 20" (457mm-609mm)
Rise Time	79 seconds	79 seconds
Motor	2HP	2HP
Minimum Bay Size	15' x 26' (4572mm x 7925mm) 15' x 28' (4572mm x 8534mm)	15' x 26' (4572mm x 7925mm) 15' x 28' (4572mm x 8534mm)



CR18N000BL

CRA18 ALIGNMENT LIFT FEATURES:

- Four wheel alignment wheelbase range from 63" up to 177"
- Two 9,000 lbs. Rolling Jacks included
- Two turning radius gauges included

CRA18 LIFT OPTIONS:

- LED runway light kit
- 30 Gallon oil drain pan
- 3-Phase motor
- Power unit cover

CR18
18,000 lbs. Capacity
General Service

CRA18
18,000 lbs. Capacity
Alignment

FEATURES:

Two model lengths available

- Multi-position lock system
- Non-skid surface on runways

CR18 LIFT OPTIONS:

- Bolt-on alignment kits
- Internal airline kit
- Drive-through ramps
- Rolling jacks
- LED runway light kit
- 30 Gallon oil drain pan
- 3-Phase motor
- Power unit cover

SPECIFICATIONS	CR18N000BL/RD CR18N001BL/RD	CRA18N110BL/RD CRA18N111BL/RD
Capacity	18,000 lbs. (8165kg)	18,000 lbs. (8165kg)
Rise	68" (1727mm)	68" (1727mm)
Maximum Wheelbase	194" (4928mm) 230" (5842mm)	194" (4928mm) 230" (5842mm)
Maximum Two Wheel Alignment	N/A	177" (4496mm) 213" (5410mm)
Min/Max Four Wheel Alignment	N/A	63" / 162" (1600mm/4115mm) 68" / 198" (1727mm/5029mm)**
Overall Length	275-3/16" (6990mm) 311-3/16" (7904mm)	275-3/16" (6990mm) 311-3/16" (7904mm)
Overall Width	137-3/4" (3498mm)	137-3/4" (3498mm)
Width Inside Columns	122" (3098mm)	121-1/2" (3086mm)
Length Between Columns	212" (5385mm) 248" (6299mm)	212" (5385mm) 248" (6299mm)
Overall Height	77-3/4" (1975mm)	77-3/4" (1975mm)
Runway Width	22" (559mm)	22" (559mm)
Runway Height	7-1/2" (191mm)	7-1/2" (191mm)
Width Between Runways (Min/Max)	43" / 46" (1092mm/1168mm)	43" / 46" (1092mm/1168mm)
Rise Time	105 seconds	105 seconds
Voltage**	208V/230V	208V/230V
Motor	2HP	2HP
Minimum Bay Size	16' x 27' (4877mm x 8230mm) 16' x 30' (4877mm x 9144mm)	16' x 27' (4877mm x 8230mm) 16' x 30' (4877mm x 9144mm)

Single phase standard *Runway radius pockets and slip plates must be reinstalled to fit smaller wheelbases



Shown CR30110100BL with optional rolling bridge jacks

CR30
30,000 lbs. Capacity

FEATURES:

Two model lengths available

- 24" wide runways
- Standard 3-phase motor
- Internal air line kit

LIFT OPTIONS:

- Turning radius gauges
- Rolling jacks
- Drive-through ramps
- LED runway light kit
- 30 Gallon oil drain pan
- 3-Phase motor

SPECIFICATIONS	CR30110100BL/RD / CR30110200BL/RD
Capacity	30,000 lbs. (12701kg)
Rise	68" (1727mm)
Maximum Wheelbase	271" (6883mm) / 307" (7797mm)
Overall Length	344-1/8" (8741mm) / 380-1/8" (9656mm)
Overall Width	148-13/16" (3780mm)
Width Inside Columns	132" (3353mm)
Length Between Columns	285" (7239mm) / 321" (8153mm)
Overall Height	84-3/4" (2153mm)
Runway Width	24" (610mm)
Runway Height	8-3/8" (213mm)
Min. / Max. Width Between Runways	41" / 48" (1041mm/1219mm)
Rise Time	105 seconds
Voltage**	208V/230V
Motor	4HP
Minimum Bay Size	16' x 33' (4877mm x 10059mm)

**Single phase standard



CR40

40,000 lbs. Capacity

FEATURES:

- Two model lengths available
- 24" wide I-beam runways
- Two 2-HP motors for tremendous lift power
- Internal air line kit
- Models with radius gauge pockets available

LIFT OPTIONS:

- Rolling jacks
- Drive-through ramps
- Power unit cover
- 40 Gallon oil drain pan

SPECIFICATIONS	CR40310000BL/RD	CR40310100BL/RD
	Capacity	40,000 lbs. (18411kg)
Rise	68" (1727mm)	
Maximum Wheelbase	300" (10008mm)	360" (9144mm)
Overall Length	394" (10465mm)	466" (11836mm)
Overall Width	171" (4343mm)	
Width Between Columns	142" (3607mm)	
Overall Height	154" (3912mm)	
Runway Width	24" (610mm)	
Runway Height	9" (229mm)	
Min. / Max. Width Between Runways	40" / 82" (1016/2083mm)	
Rise Time	100 seconds	
Voltage/AMPS**	208/230V single-phase, 40 amps;	
	208/230V 3-phase 25 amps;	
	460V 3-phase, 15 amps	
Motor	2HP X 2	

** Single phase standard; 3-phase available at additional cost



Battery operated DC power with 110V on-board charger

- Fully hydraulic with protected piston rods
- Locks in each column
- Internal airline kit

LIFT OPTIONS:

- Rolling bridge jacks
- High efficiency LED light kit
- Drive-through ramps
- Wheel kit
- Shim kit

CR50

50,000 lbs. Capacity

CR60

60,000 lbs. Capacity

FEATURES:

Two model lengths available
Patented control system operates lift from any column.

No cables, chains or sheaves

THE CONTROL SYSTEM OFFERS:

- Position memory to configure repeatable lifting cycles
- Visual confirmation of each column's status and lift height
- Level lifting within 3" at each column
- Oversized "E-Stop" emergency stop button
- Audible descent alarm for added safety

SPECIFICATIONS	CR50MU000RD	CR60MU000RD	CR50MU001RD	CR60MU001RD
	Capacity	50,000 lbs. (22680kg)	60,000 lbs. (27216kg)	
Maximum Rise	78" (1981mm)	78" (1981mm)		
Maximum Wheelbase	336" (8534mm)	336" (8534mm)		
	396" (10058mm)	396" (10058mm)		
Overall Length	427" (10846mm)	427" (10846mm)		
	487" (12370mm)	487" (12370mm)		
Overall Width	189" (4800mm)	189" (4800mm)		
Width between Columns	142" (3606mm)	142" (3606mm)		
Column height	144-3/4" (3912mm)	144-3/4" (3912mm)		
Runway Width	28" (711mm)	28" (711mm)		
Width between Runways	45" (1143mm)	45" (1143mm)		
Rise Time	65 seconds	65 seconds		
Ramp Angle	10 degrees	10 degrees		

Lifts available in red only



FCH13

13,000 lbs.

Column Capacity

FCH18

18,000 lbs.

Column Capacity

FEATURES:

Two, four, six or eight mobile column configurations can accommodate heavy duty trucks up to 144,000 pounds

PATENTED CONTROL SYSTEM OFFERS:

- Position memory to configure repeatable lifting cycles
- Visual confirmation of each column's status
- Level lifting within 3" at each column
- Oversized "E-Stop" emergency stop button
- Audible descent alarm for added safety
- Programmable height limiter
- Battery indicator

LIFT OPTIONS:

- High efficiency LED light kit
- Weight gauge
- Reducer sleeves for forks
- Large wheel riser kit

Battery operated DC power with 110V on-board charger

- Fully hydraulic with protected piston rods
- Locks in each column
- Retractable cord reels (FCH18) with quick connect cables
- Automatic steering / braking system
- Adjustable lifting forks
- Usable on any concrete surface

SPECIFICATIONS	FCH418	FCH618	FCH818
	Column configuration	4	6
18,000 lb. Capacity	72,000 lbs. (32658kg)	108,000 lbs. (48987kg)	144,000 lbs. (65317kg)
SPECIFICATIONS	FCH413	FCH613	FCH813
	Column configuration	4	6
13,000 lb. Capacity	52,000 lbs. (23587kg)	78,000 lbs. (35380kg)	104,000 lbs. (47174kg)
Rise	FCH18 - 70" (1778mm)		
	FCH13 - 69" (1760mm)		
Column width	FCH18 - 45-1/2" (1156mm)		
	FCH13 - 43" (1092mm)		
Wheel rim size	9" to 25" (228 to 610mm)		
Clearance Fork to Column	10" (254mm)		
Rise Time	FCH18 - 78 seconds		
	FCH13 - 68 seconds		
Charging Voltage	110v charger* 2.5 amps		

Lifts available in red only



EFP9P000M

EFP8

8,000 lbs. Capacity

EFP9

9,000 lbs. Capacity

FEATURES:

Commercial grade lifts.
Perfect for home use

- Exclusive adjustable lock ladder system
- Multi-position locks allow runways to be level at any lock position
- Single point lock release
- Powder coat finish
- Lifts available in black only

INCLUDES:

- Steel approach ramps
- Wheel caster kit
- Jack tray
- Drip trays

SPECIFICATIONS	EFP8P000M	EFP9P000M
Capacity	8,000 lbs. (3628kg)	9,000 lbs. (4082kg)
Rise	72" (1828mm)	84" (2133mm)
Overall length with approach ramps	207-1/2" (5270mm)	225-1/2" (5727)
Overall length without approach ramps	175-1/2" (4457mm)	192-1/2" (4889)
Overall width without motor	103-1/2" (2628mm)	121" (3073)
Approach ramp Length	32" (812mm)	36-1/4" (920mm)
Runway width	18-1/2" (469mm)	20" (508mm)
Runway length	169-1/2" (4305mm)	188" (4775)
Runway height	4-1/2" (114mm)	4-3/4" (120mm)
Height of columns	81-1/2" (2070mm)	97" (2463mm)
Clearance between columns	94" (2387mm)	109-1/2" (2781)
Clearance between runways	38" (965mm)	39" (990mm)
Outside runway to outside runway	74" (1879mm)	79" (2006mm)
Clearance under runway	68" (1727mm)	79-1/4" (2012mm)
Motor	115VAC, 1HP	115VAC, 1HP

6000MRL

6,000 lbs. Capacity

FEATURES:

- Portable, space-saving scissor-style design
- Dual hydraulic cylinders
- Swing arms with pad adapters
- Seven locking positions from 6 - 1/2" to 54"
- Four tall adapters included



SPECIFICATIONS	6000MRLBK
Capacity	6,000 lbs. (2721kg)
Maximum Rise	54" (1372mm)
Lowered Height	5" (127mm)
Overall Width	41" (1041mm)
Overall Length	83" (2108mm)
Voltage	115v
Shipping Weight	1,000 lbs. (453kg)

Lifts available in black only

MID / LOW RISE LIFTS ▶ 6,000 lbs. to 10,000 lbs. CAPACITIES



TL10111000BL

TL07

7,000 lbs. Capacity

TL10

10,000 lbs. Capacity

FEATURES:

- Drive-over ramps and side rails provide the width to support wider vehicles while approaching and exiting the lift
- Dual lifting cylinders provide the required power
 - The TL07 comes with four 3" rubber blocks and four 1.5" rubber blocks for added height
 - The TL10 comes with four 3-position adapters, four 3" rubber blocks and four 1.5" rubber blocks for added height

SPECIFICATIONS	TL07111000BL/RD	TL10111000BL/RD
Capacity	7,000 lbs. (3175kg)	10,000 lbs. (4535kg)
Overall Length	90-1/2" (2298mm)	90-1/2" (2298mm)
Overall Width	78-1/2" (1993mm)	78-1/2" (1993mm)
Width Between Platforms	22-3/4" (577mm)	22-3/4" (577mm)
Length of Platforms	51-1/4" (1301mm)	51-1/4" (1301mm)
Length of Pad	17" (431mm)	22-3/4" (577mm)
Outside Width of Platforms	70-3/4" (1797mm)	70-3/4" (1797mm)
Horizontal Movement During Rise	16" (406mm)	16" (406mm)
Collapsed Height	4" (101mm)	4" (101mm)
Locking Leg Heights	13-3/8" (339mm) 17-3/8" (441mm) 21-3/8" (542mm)	13-3/8" (339mm) 17-3/8" (441mm) 21-3/8" (542mm)
Voltage/Amps	115V, 20 amps	115V, 20 amps
Speed of Rise	40 seconds	40 seconds
RISE HIGH STEP	N/A	30-5/16" (769mm)
RISE MID STEP	N/A	28-5/16" (719mm)
RISE LOW STEP	N/A	26-5/16" (668mm)
RISE TALL PAD	24-3/4" (628mm)	24-3/4" (628mm)
RISE SHORT PAD	23-1/4" (590mm)	23-1/4" (590mm)
RISE FLAT	21-3/4" (552mm)	21-3/4" (552mm)

MOTORCYCLE LIFTS ▶ 1,000 lbs. CAPACITIES

1000MCL

1,000 lbs. Capacity

1000MCLDT

1,000 lbs. Capacity
DROP TAIL



DROP TAIL
1000MCLDTMFBK



1000MCLMFbk

FEATURES:

- Two 12" removable side platform extensions create a 48" wide runway deck
- Adjustable front wheel vise
- Foot pedal controlled air valve
- Portable

SPECIFICATIONS	1000MCLMFbk 1000MCLDTMFBK
Capacity	1,000 lbs. (435kg)
Maximum Rise	33" (838mm)
Lowered Height	7-1/4" (184mm) 24" (610mm)
Overall Width	48" (1219mm) w/side extensions
Overall Length	113" (2870mm) w/ramp 93" (2362mm) w/o ramp
Compressed Air Connection	90 -110psi
Shipping Weight	690 lbs. (313kg)

Lifts available in black only

1000MCLDT FEATURES:

- DROP TAIL model - Removable rear drop-tail panel for wheel and tire service
- 1,000 lbs. capacity wheel service jack included

LIFT ACCESSORIES *PRODUCTIVITY AND PERFORMANCE*

FOR COMPLETE PRODUCT INFORMATION, VISIT US AT WWW.FORWARDLIFT.COM

ROLLING JACKS

- RJ35BK** Hydraulic Hand Pump Rolling Jack / EFP8 Lift / 3,500 lbs. CAPACITY
RRJ45G Hydraulic Hand Pump Rolling Jack / EFP9 Lift / 4,500 lbs. CAPACITY
RRJ70GBK Pneumatic / Hydraulic Rolling Jack / 7,000 lbs. CAPACITY
RJ901000YBK Pneumatic / Hydraulic Rolling Jack for use with CR14 Lift models with Jack Rails / 9,000 lbs. CAPACITY
FC5760-14 Airline Kit for CR14 / CRO14 / CRO14EL2
RJ151BK Pneumatic / Hydraulic Rolling Jack for use with CR30 Lift models with Jack Rails / 15,000 lbs. CAPACITY
RJ153BK Pneumatic / Hydraulic Rolling Jack for use with CR30 Lift 1-3/4" lower profile than RJ151BK, with universal adapters / 15,000 lbs. CAPACITY
RJ2001000BK Pneumatic / Hydraulic Rolling Jack CR40 Lift / 20,000 lbs. CAPACITY
RJ2501000BK Pneumatic / Hydraulic Rolling Jack CR50M / CR60M Lifts / 25,000 lbs. CAPACITY

RAMP KITS

- S100150Y** STANDARD Approach / Drive Thru Ramps (Set of Two) For CR14 Lifts
S100151Y STANDARD Approach / Drive Thru Ramps (Set of Two) For CRO14 / OR14 / CR14EL Lifts
S100152Y EXTENDED Approach / Drive Thru Ramps (Set of Two) For CR14 Lifts
FC5780-3 24" Wide, 47" Long Floor Mounted Approach / Drive Thru Ramps (Set of Two) For CR28 / CR30 Models
134K01 24" Wide 72" Long Floor Mounted Approach / Drive Thru Ramps (Set of Two) For CR40 Models *MUST order 2500K01 Auto Stop Kit with #134K01*
M140099RD Drive-Thru Ramp Kit for CR50/CR60
APRAMP10DTKITRD Drive-Thru Ramp Kit - 10' Ramps for low profile vehicles CR50 / CR60 Lifts

ALIGNMENT LIFT OPTIONS

- S100136M** CR14 / CRO14 Bolt On Alignment Kit / 14K General Service Lift to Alignment Lift - DOES NOT INCLUDE FRONT TURN PLATES.
S100137M CR14EL / CRO14EL Bolt On Alignment Kit / 14K General Service Lift to Alignment Lift - DOES NOT INCLUDE FRONT TURN PLATES.
S100183 Efficiency Kit for CR14 / CRO14 Lifts - Includes 2 rolling jacks and internal air line kit
S100138 CR18 Bolt On Alignment Kit / 18K General Service Lift to Alignment Lift
S100139 CR18-3 Bolt On Alignment Kit / 18K General Service Lift to Alignment Lift
S100184 Efficiency Kit for CR18 Lifts - Includes two rolling jacks and internal air line kit
TT1000YKIT Standard Turning Radius Gauge Kit / Includes Two (2) Turning Radius Gauges and Four Retaining Bars / 4,500lbs. Capacity per Gauge (2041kg)
TT1001KIT Stainless Steel Turning Radius Gauge Kit / Includes Two (2) Turning Radius Gauges and Four Retaining Bars / 3,000lbs. Capacity per Gauge (1360kg)
PK304FC7117Y Turntable Spacer for Image Aligners - Roll Back Kit / Set of Two (2)

ACCESSORIES and OPTIONS

TWO POST LIFTS

- FA5911BK** Air/ Electric Work Station with Filter/Regulator/Lubricator for 2 post lifts
T100285 Adjustable Frame Contact Adapter (Qty 4 T110564ZN with Brackets) For I10, DP10 Lifts
FJ6263 Wide drop in adapter for DP10/I10 lifts with 1-1/4" diameter pilot for lifting 2019 Chevrolet Pick-ups / Includes two (2) FJ6248 adapters and two (2) FJ6262 1-1/4" to 1-1/2" adapter extenders / 1-3/4" tall

- FJ6245YKIT** Kit of four FJ6245Y Round Rubber Adapters, bracket and hardware
TPB10-D Door Bumper Kit (Pair) for I10 Lifts
T140265 Padded Knee Saver
FA5974 Wheel Wing Kit (Set of 2) includes 2 dishes, shims, adjustable to fit various 2 post lifts. 100 lb. capacity per wing. The wheel wing holds a tire at lift arm height - handy for tire rotations and brake jobs.
FA5702 Handheld Rechargeable Tech Light
FA5701 2-Post Light Kit, two (2) 32" long light wands with 95 LEDs each. 8 magnetic clips included. Input voltage 100-240V AC
RS4 2-Post Jack Stand, Screw-Type, Adjustable 55.5" - 84" Range (1410mm-2133mm) 18,000 lbs. CAPACITY

FOUR POST LIFTS

- FA915KIT** Air/ Electric Work Station With Filter/Regulator/Lubricator for 4 post lifts
FA5700 4-Post Light Kit, four (4) 48" long light wands with 216 LEDs each. 8 magnetic clips included. Input voltage 100-240V AC

- FA7815** Laser Guided Spotting Kit for 2 Post and 4 Post Lifts - Motion activated vehicle spotting system. Complete with motion sensor, mounting hardware and instructions.

MOTORCYCLE

- BJ10BK** Jack for Motorcycle lift

MOBILE COLUMN

- ML41YL** Saddle Cross Beam With Two (2) Support Blocks for frame pick-up 32,000 lbs Capacity at 72" adapter spread. 24,000 lbs. Capacity at 49" adapter spread.
M140070YL Low Profile Cross Beam with Two (2) Support Blocks for frame pick-up 30,000 lbs Capacity at 49" adapter spread. 21,000 lbs. Capacity at 25" adapter spread.
RS18YL Jack Stand, Screw-Type, Adjustable 56.1" - 82.3" Range (1425mm-2090mm) 18,000 lbs. CAPACITY
RS1852SYL Jack Stand, Screw-Type, Adjustable 34.3" - 55.5" Range (870mm - 1410mm) 18,000 lbs. CAPACITY
RS36SYL Jack Stand, Screw-Type, Adjustable 55.31" - 82.28" Range (1405mm - 2090mm) 36,000 lbs. CAPACITY
M120304BK Large wheel adapter (per column)
M140030 Riser Kit - Tire ramps to allow proper fork placement (per column)
M140148BK LED Service Lamps - Operates from column battery power (per column)
M140019 Weight gauge (per column)
M140157 Weight gauge for Monarch power unit (per column)
M140071YL Wheel Adapters (set of 4)
M140078YL Fore and aft, frame engaging lift kit for use with (2) FCH4 or RCH Series Columns. Maximum capacity 7,500 lbs per FCH4 Column.

DRAIN PANS / DRIVE ON LIFTS

- FC5967BK30** Gallon Mobile Oil Drain Pan for CR14,OR14, CR18 Lifts
FC5968BK Low Profile 30 Gallon Mobile Oil Drain Pan for CR30 Lifts
213000BK 40 Gallon Mobile Oil Drain Pan for CR40 Lifts

WARRANTY

- 100W02** 24 Month, Extended Parts Warranty (All models)



996 Industrial Drive
Madison, IN 47250

Phone: 800.423.1722
Fax: 812.273.7329

www.forwardlift.com



Lit# Forward Product iCatalog.2019.10 ©2019 Vehicle Service GroupSM

All rights reserved. Unless otherwise indicated, Forward Lift, Vehicle Service GroupSM, Dover and all other trademarks are property of Dover Corporation and its affiliates. Printed in the U.S.A.